NETSPA CHILLER

These instructions are in addition to the instructions supplied with each component of the set. Its purpose is to explain the interaction between the components and the specific use of the complete assembly.

1. Packing

Your NETSPA CHILLER is delivered in a set of 3 boxes. By assembling the following elements, you will be able to cool the water in your pool electrically. You'll be able to take advantage of the *chiller* function, which provides invigorating and restorative cold baths, without having to use 50kg of ice cubes for each bath.

Box 1	Box 2	Box 3
Basin Järvi / UFC 1 place	Circulation pump and hoses	Heat pump Chiller

2. Hydraulic connection

Once you have prepared the various components in accordance with their respective instructions, you need to make the hydraulic connections between the sump, the boiler block and the circulation pump.

⚠ Switch off the water and electricity supply during installation.

1. Connect the water hose coming out of the spa (bottom) to the water inlet of the circulation pump*.
2. Connect the water hose coming out of the circulation pump* to the water inlet (IN)* of the chiller block using one of the connection hoses supplied in box 2.
3. Connect the water hose at the outlet (OUT) of the chiller block* to the water inlet of the spa (top).

*If necessary, add Teflon (PTFE tape) to the threaded fittings to improve tightness.

⚠ Before filling the basin, remove the 2 inner plugs and screw the filter of the basin on its low nozzle.

When the water level is between the outlet and inlet of the basin, start the pump to purge the air in the system. Then continue to the required level.





3. Electrical connection

⚠ The electrical installation must comply with standard NF C 15-100.

⚠ Do not use a power strip or extension lead.

Connect the appliances to 2 separate sockets protected by a 30mA earth leakage switch.

4. Chiller block settings

To take advantage of the chiller functions (T° < 5°C), advanced parameter C11 of the chiller block must be set to 3°C. This setting allows cooling down to 3°C. To change this setting, refer to your SPAWER heat pump manual.

1. Switch off the heat pump
2. Press the button ⏻ for 3 seconds to view the parameters.
3. Use the ▲ and ▼ arrows to navigate to parameter C11.
4. Confirm by pressing the button ☼.
5. Change the value using the ▲ and ▼ arrows.
6. Confirm the new value by pressing the button ☼.

Dear customer,

A question? A problem? Or simply register your warranty, find us on our website:

https://assistance.poolstar.fr/

Thank you for you trust and support. Happy bathing!

Your personal information is processed in accordance with the French Data Protection Act of 06 January 1978 and will not be shared with 3rd parties.