





The ultimate solution to control your spa's temperature




Up to 75% energy savings compared to a standard heater



Reversible Hot / cold



4 good reasons to choose a Spawer



1. Reduce your consumption

Enjoy your spa while reducing your electricity bill

Expect over € 500* of electricity over a year when your spa water is heated with the integrated electric heater as it consumes around kW 2.444.

When using a Spawer heat pump, your spa's average consumption is considerably reduced down to kW 420*. You therefore save around € 400** per year and your heat pump quickly pays for itself.

^{**} Estimate for a heat pump with an average COP of 5.



2. Plan your session

Control your spa's temperature from a distance with the Smartlife app

Connect yourself from the office and plan your relaxation session for the evening. You can change water temperature, mode (heating/cooling) and timing before you even get home.

3. An ideal temperature year-round

With the reversible mode, cooler water when it is warmer outside

Spawer is your companion in the winter to heat up your spa while saving on energy consumption and in the summer to cool down your spa water. No need to add cold water to your spa any more. Spawer adapts itself to your needs.



4. Special Chiller function on the O'Spa

O'Spa, the most efficient in chiller mode

The "Chiller" function effectively cools down the water, providing a refreshing bathing experience with a drop in temperature up to 3°C. Ice bath therapy is increasingly recognised as a way of harnessing the body's natural recuperative powers.



^{*} Approximate estimate for a 5-person spa with a 1,000-litre volume.

ENJOY YOUR SPA

Hot **Gold**





All in one!

AUTOMATIC MODE

Your heat pump will reach and maintain the required temperature by selecting its own mode of operation (heating / cooling).

INTEGRATED WIFI

Your connected heat pump can be controlled remotely, as you wish, using the Smartlife app.

STAND-ALONE INSTALLATION

2 relays available and compatible with the spa's range of control systems

HEATING RELAY

Your heat pump, in extreme weather conditions, will decide or not to used the existing heater

PUMP RELAY

Your heat pump will control the auxiliary circulation pump, making your installation fully stand-alone



ICESPA 5kW 7kW

The power of Full Inverter & EVI efficiency right down to -25°C



Ideal all seasons



Reversible hot/cold



Control through a wifi connection



Remote touch screen



AT -10°C, the heat pump avoids all use of the electric heater

The IceSpa is a heat pump for spase specially conceived for the most extreme climate, the most powerful on the market at low temperature: 3.3 kW at Air -10 / Water 38°C thanks to its EVI (Enhanced Vapour Injection) compressor.

With a COP of 2, even at -10°C the IceSpa is 2 times cheaper than the electric heater.

Operating down to -25°C, you can heat up your spa right in the middle of snow peaks and enjoy the view in complete peace. Its Full Inverter technology will reduce your energy consumption up to 75% at an equivalent power consumption compared to an electric heater! Easy to install, the IceSpa is compatible with all hot tubs and connects itself as easily.

Ideal for swim spas and nordic baths, this heat pump will meet your expectations.

EVI TECHNOLOGY



L'EVI (Enhanced Vapour Injection) improves the **energy efficiency** of refrigeration and air conditioning systems by **injecting additiona vapor** into the compressor at low temperatures.

It is thanks to this **innovative technology** that the Ice Spa is able to perform so well in **extreme weather conditions.**



COMPACT DIMENSIONS AND WIFI CONNECTION

Remote control







Remote touch screen

included with the 5 kW en option avec la 7 kW



Hydraulic connecting kit* optional

* Non-contractual photos



Control relay as an option





5kW

7kW

Air 26°C Water 26°C Hygro 70°C	Output power	5.4 ~ 2.50 kW	7.2 ~ 2.90 kW
	Power consumption	1 ~ 0.2 kW	1.1 ~ 0.21 kW
	COP	5.3 ~ 13.9	6.7 ~ 13.81
Air -10°C Water 38°C Hygro 70°C	Output power	3 kW	3.3 kW
	Power consumption	1.5 kW	1.6 kW
	СОР	2	2.2
Air 15°C Water 38°C Hygro 70°C	Output power	3.7~1.8 kW	4.6 ~ 2.21 kW
	Power consumption	1.2~0.3 kW	1.3 ~ 0.39 kW
	COP	3 ~ 5.6	3.6 ~ 5.67
Operating range		-25°C to 43°C	
Optimum flow (3/h)		2.31	3.01
Dimensions (cm)		60 x 39 x 42.3	71 x 49 x 50
Noise level at 10 m (dB)		< 32	< 34
Hydraulic connections (mm)		1"male / ø32 - ø38 (connectors provided)	
Operating modes		Heating / Cooling / Auto	
Warranty		3 years	



O'SPA 3kW 5kW 7kW

Ultra versatile heat pump for spas



Ideal hot and temperate climates



Reversible hot/cold



Control through a wifi connection



Ultra compact





COMPACT AND EFFICIENT

O'Spa is a heat pump for spas that can save you up to **75% in energy consumption** when heating your spa compared to a conventional electric heater (at an equivalent power consumption).

The O'Spa can be installed on any type of hot tub and nordic bath in order to take over the existing electric heater and **optimize**

the increase in temperature

inside your spa. You only need to connect it and its relay will manage the electric heater initially integrated to the spa.

COMPACT DIMENSIONS AND WIFI CONNECTION

Remote control









Hydraulic connecting kit* (optional)



Control relay included

^{*} Non-contractual photos

NEW FUNCTION

THE CHILLER



O'SPA DUAL FUNCTION

O'Spa is the essential choice for wellness enthusiasts, offering a dual function: heating and cooling.

The **Chiller function** effectively cools the water, providing a **refreshing bathing experience** thanks to a drop in temperature of up to **3°C**.

lce bath **therapy** is increasingly recognised as a way of harnessing **the body's natural recuperative powers**.

BENEFITS INCLUDE:

- Improved blood circulation
- Reduced arterial hypertension
- Reinforced immune system
- Muscular recovery
- Relaxation and stress reduction



The **heating function** increases the water temperature, saving up to **75% energy** compared to a conventional electric heater. The O'Spa can be fitted to all types of spa and Nordic bath, optimising the temperature rise of your spa for optimum comfort and experience.

This unique dual function makes the O'Spa a high-performance, versatile **piece of equipment**, that meets the demanding needs of users, whatever their environment.





5 kW

7 kW

Recommended climate		Hot	Temperate	
Air 26°C Water 26°C Hygro 80°C	Output power	3 kW	5 kW	7 kW
	Power consumption	0.58 kW	0.97 kW	1.35 kW
	СОР	5.15	5.2	5.2
Air 15°C Water 38°C Hygro 70°C	Output power	1.8 kW	3.3 kW	3.90 kW
	Power consumption	0.6 kW	1.1 kW	1.39 kW
	СОР	2.77	3	2.80
Air 35°C Water 27°C Hygro 70°C	Output power	1.5 kW	1.9 kW	3.50 kW
	Power consumption	0.53 kW	1 kW	1.38 kW
	EER	1.8	1.9	2.5
Chilling time for 200L of water from 23°C to 5°C.		5 h	3 h	2 h
Operating range		-7°C to 43°C		
Optimum flow (3/h)		1.30	2.16	3.01
Dimensions (cm)		44 x 38 x 42.3		60 x 39 x 42.3
Noise level at 10 m (dB)		<30	<32	<34
Hydraulic connections (mm)		1"male / ø32 - ø38 (connectors provided)		
Operating modes		Heating / Cooling / Auto		
Warranty		2 years		

Non-contractual data subject to change



More information on our website:

poolex.fr/en